


Kemper CO₂ Storage Complex: Pipeline and Surface Facility Design Considerations

*Presentation for Project ECO2S Workshop
at 2023 CO2GeoNet Conference*

Katherine Dombrowski, Joe Lundeen, Trimeric
Jean Everett, Leon Proper, Ryan Almerico, PCS
October 2, 2023



Disclaimer

Parts of this presentation are based upon work supported by the Department of Energy and was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Trimeric Corporation: Process engineering services

- Founded in 2003 in Buda, TX
- Diversified across industries, specialized in process engineering
- CO₂ capture & processing expertise
 - Pipeline flow analysis
 - Compression and dehydration
 - Pump skids for injection tests
 - Liquefaction and distillation
 - EOR facilities for Gas plant/recycle
 - Source assessments for Carbon SAFE



1 MM tonne/yr facility design. Blower (left) and compressor (right) skids

- Capture from Power Plants
- Capture from Industrial Sources
- Process simulation
- TEAs
- Food and beverage grade CO₂ facilities
- Process safety

Project Consulting Services, Inc.: PCS

- ❑ Founded in 1992 in New Orleans, LA
- ❑ Provider of project and design services to the pipeline and pipeline facilities industry
- ❑ Thousands of miles of pipeline development projects onshore and offshore
- ❑ Over 20 years of CO₂ transportation expertise
 - Approximately 600 miles of CO₂ pipelines, multiple pump, meter and mainline valve stations
 - A history of studies and early-phase development
 - ❑ Feasibility, pre-FEED and FEED projects
 - Expertise in transporting CO₂ via pipeline
 - ❑ Routing
 - ❑ Permitting
 - ❑ Procurement
 - ❑ Construction



Plant Ratcliffe is closest CO₂ source to Kemper Storage Complex

- Southern Company, Mississippi Power
- NGCC: 2 CT x 1 ST
- 770 MWe nameplate
- Max CO₂ rate: 287 tonne/hr
- Max CO₂ rate: 6,888 t/d
- Min CO₂ rate: 133 tonne/hr
- 85% annual capacity factor
- 2.1 Mtpa
- 64 Mt over 30 years to Storage



Kemper Storage Complex is near several other large CO₂ sources



Power Plant	Nameplate Generating Capacity (MWe)	Annual CO ₂ (Mtpa)	Approx Pipeline Distance (km)
Ratcliffe (NGCC)	770	2.1	13
Daniel (NGCC)	1,070	2.9	290
Miller (coal)	2,640	17.3	240

Initial concept for 2 wells for Plant Ratcliffe

- Ratcliffe max CO₂: 6,888 t/d
- Injection wells at 19-2 and 32-1
 - Each designed for 4,000 t/d
 - Required injection P
 - > 1,200 psig
 - > 8.4 MPa
 - > 84 bara



Pipeline FEED Study

- FEED = Front-End Engineering and Design
- 13-km route at Kemper Complex: from Ratcliffe + future phases
- Early-phase, desktop study; no field survey
- Environmental Information already gathered by ECT:
 - Land use
 - Hydrologic and Geologic/Soil conditions
 - Vegetation and wildlife resources
 - Socioeconomic conditions
 - Historic/Cultural resources

Pipeline FEED Study Deliverables

- Basis of Design
- Permit Matrix
- Desktop route study
- Desktop geotechnical study
- Route map books
- PFDs
- P&IDs
- Risk register
- Project management plan
- Project schedule
- Hydraulic analysis (primary and optional routes)
- Bill of Materials
- Total Installed Cost (Class 3)
- Report narrative

FEED Study Results presented here are under review, and not yet finalized

Hydraulic Modeling Parameters

□ CO₂ from Plant Ratcliffe:

- Max flow rate: 362 tonne/hr
- Normal operating conditions: 1,700 psig, 120°F

□ Well Specification:

- Pressure required: 1,500 psig
- Maximum injection rate at each well of 181 tonne/hour



□ Composition modeled

- Worst case for hydraulic model
- Plant Ratcliffe CO₂ will have higher purity

Component	Modeled Mole Basis
CO ₂	95.9337%
H ₂ O	630 ppmv
H ₂ S	20 ppmv
N ₂	2.0%
CH ₄	2.0%
O ₂	13 ppmv
SUM	100%


PLANT RATCLIFFE STATION

FROM PLANT RATCLIFFE MISSISSIPPI POWER





$Q_{max}=362$ TONNE/H
 $P_{max}=1,800$ PSIG

SITE BOUNDARY




MPC 19-2 STATION




GATHERING & DISTRIBUTION HUB

[FUTURE CONNECTIONS]
 $Q_{max}=362$ TONNE/H, EACH







FUTURE CONNECTIONS

MPC 19-2 WELL PAD




$Q_{max}=181$ TONNE/H, EACH








SITE BOUNDARY

MPC 32-1 WELL PAD



$Q_{max}=181$ TONNE/H, EACH



SITE BOUNDARY

MPC 32-1 STATION


PFD ABBREVIATIONS

BD:	BLOWDOWN
B.F.:	BLIND FLANGE
NC:	NORMALLY CLOSED
P:	PRESSURE
Q:	FLOW

THIS DRAWING IS FOR REVIEW PURPOSES ONLY AND SHALL NOT BE USED FOR BIDDING, CONSTRUCTION, PERMITTING OR REDECORATION PURPOSES.


DRAFT RESULTS

Plant Ratcliffe




Metering Station

PIG Launcher




Gathering/Distribution Hub



Metering Station

Wellhead



DRAFT RESULTS

THIS DRAWING IS FOR REVIEW PURPOSES ONLY AND SHALL NOT BE USED FOR BEING CONSTRUCTION, PERMITTING OR REDESIGNATION PURPOSES.

PROJECT CONSULTING SERVICES INC.
1000 WEST GARDNER AVE. SUITE 100
DENVER, CO 80202-3144
TEL: 303.733.4444
WWW.PCS-CONSULTING.COM




Route Selected to Mitigate Permitting and Construction risks


- ❑ Other Factors: length, hydraulics, water crossings, soils, topography, public opinion, population density, industrial development areas
- ❑ Internal environmental review to minimize impacts to wetlands and archaeological features
 - > 100' buffer around cultural/archaeological features
 - Wetlands crossed include Freshwater Emergent Wetland and Freshwater Forested/Shrub Wetland

Adjusted route for constructability and workspace requirements


- ❑ Permanent Easement: 50 feet
- ❑ Temporary Workspace (TWS): Working Side 15 feet / Spoil Side 10 feet
- ❑ Additional TWS: each unique, most common is 25 feet wide



Sheet 7



DRAFT RESULTS



1 inch equals 250 feet

0 125 250 500 Feet

1) World Imagery: ESRI, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AeroGRID, IGN, and the GIS User Community.
 2) Coordinate System: NAD 1983 2011 StatePlane Mississippi East FIPS 2301 Ft US
 3) Map Size: 11"x17" Date: 8/17/2023

- Mileposts
- Bore
- Drill
- Open Cut
- ▲ Injection Well
- NHD Flow Lines
- NHD Waterbodies
- NWI Wetlands
- Hub Site
- Permanent Easement
- Temporary Workspace
- Additional Temporary Workspace
- Contours
- Parcel Boundaries
- Archaeology Sites



Advanced Resources International, Inc (ARI) CO2 Pipeline

Kemper County, Mississippi

PS

SHEET: 7 OF 11




Route Corridor Summary

- Total Length = 43,035 linear feet (LF)
- Est No of HDDs = 3 (5,400 LF) [horizontal directional drilling]
- Est No of Bores = 16 (1,800 LF)
- Est No of Road Crossings = 4
- Est. No of Bends = 20
- No of Pipeline Crossings = 0

Plant Ratcliffe Station Conceptual Layout

100' x 100'

Crushed limestone pad




DRAFT RESULTS

Hub and Well Pad Conceptual Layout

540' x 360'


Crushed limestone pad

Space for future injection pump



Schedule

ECO2S FEED Project Schedule



Risks and Information Gaps

- ❑ Line Pipe: Procure pipe as quickly as possible to guard against price increases
- ❑ Specialty Items: Market availability of valves
- ❑ Installation: Access and workspace approval from landowners, permitting delays, availability of contractors, weather events
- ❑ Construction Mats: Large and considerable project cost, with different quality of mats for different areas

Contact Info and Acknowledgments

- Trimeric Corporation (www.trimeric.com)
 - Katherine.Dombrowski@trimeric.com
 - Joe Lundeen, Roz Jones, Ray McKaskle
- Project Consulting Services (www.projectconsulting.com)
 - Leon Proper: lproper@projectconsulting.com
 - Jean Everett, Ryan Almerico
- Advanced Resources International
 - George Koperna, Dave Riestenberg
- Other ECO2S project team members: SSEB, Southern Company, ECT, Crescent Resource Innovation

